

# **NETL Life Cycle Inventory Data Process Documentation File**

**Process Name:** Shuttle Car Construction **Reference Flow:** 1 pcs of Shuttle Car, Construction **Brief Description:** The amount of steel used in the construction of one shuttle car to be used to haul coal from the working mine face to the conveyor belt in underground mining. **Section I: Meta Data** US **Geographical Coverage: Region:** Southern Illinois **Year Data Best Represents:** 2007 **Process Type:** Basic Process (BP) **Process Scope:** Gate-to-Gate Process (GG) **Allocation Applied:** No **Completeness:** Individual Relevant Flows Captured Flows Aggregated in Data Set: Process ☐ Energy Use ☐ Energy P&D ☐ Material P&D **Relevant Output Flows Included in Data Set:** ☐ Greenhouse Gases ☐ Criteria Air □ Other Releases to Air: Inorganic ☐ Organic Emissions □ Other Releases to Water: ■ Water Consumption ■ Water Demand (throughput) Water Usage: ☐ Inorganic Releases ☐ Organic Releases □ Other Releases to Soil: **Adjustable Process Parameters:** Steel\_Cold\_Roll [kg/pcs] Kilograms of cold-rolled steel per pieces of shuttle car (one shuttle car) [pcs/pcs] Pieces of shuttle car per Shut\_Car\_Const pieces of shuttle car (reference flow of

one shuttle car0



#### **Tracked Input Flows:**

Steel cold rolled, PE [Technosphere]

## **Tracked Output Flows:**

Shuttle Car, Construction [Insert] Reference flow

## **Section II: Process Description**

#### **Associated Documentation**

This unit process is composed of this document and the data sheet (DS) Stage1\_C\_Shuttle\_Car\_Construction\_2015.01.xlsx, which provides additional details regarding relevant calculations, data quality, and references.


## **Goal and Scope**

This unit process provides a summary of relevant input and output flows associated with the construction of an underground coal mine shuttle car. Inputs include cold-rolled steel and outputs include one shuttle car. The reference flow of this unit process is: 1 pcs of Shuttle Car, Construction

## **Boundary and Description**

Shuttle cars are used in underground coal mining to move excavated coal from the excavated coal face to conveyor belts. This unit process includes the major materials and the masses of those materials required to construct one coal shuttle car. The data for the shuttle car comes from manufacturer specifications for shuttle cars (Phillips Machine Service, 2007a, 2007b, 2007c, 2007d). Cold-rolled steel is the assumed input material.

The mass of the shuttle car is based on its empty weight. Batteries for the shuttle car were not separated from the overall weight of the car and, as a result, battery weight is included in the total weight of steel required for the shuttle car. This is a data limitation. The weights of four different sizes of shuttle cars from Phillips Machine Service were obtained and averaged. The cars ranged in capacity from 7.2 cubic meters to 16.1 cubic meters. Each car has an empty weight between 24.5 and 32.7 metric tonnes (Phillips Machine Service, 2007a, 2007b, 2007c, 2007d). These minimum and maximum values were averaged to calculate an average of 28.6 metric tonnes, the empty weight of a single shuttle car.



**Figure 1: Unit Process Scope and Boundary** 



## **Table 1: Unit Process Input and Output Flows**

Flow Name	Value	Units (Per Reference Flow)
Inputs		
Steel cold rolled, PE	28,600.00	kg
Outputs		
Shuttle Car, Construction [Insert]	1.00	pcs

<sup>\*</sup> **Bold face** clarifies that the value shown *does not* include upstream environmental flows.

## **Embedded Unit Processes**

None.

## Re

eferences	
Phillips Machine Service 2007a	Phillips Machine Service. (2007). The Freedom Car Family: FC12 Shuttle Coal Hauler. Phillips Machine Service. http://www.phillipsmachine.com/pdf/FC12.PDF (accessed December 14, 2009).
Phillips Machine Service 2007b	Phillips Machine Service. (2007). The Freedom Car Family: FC16 Shuttle Coal Hauler. Phillips Machine Service. http://www.phillipsmachine.com/pdf/FC16.PDF (accessed December 14, 2009).
Phillips Machine Service 2007c	Phillips Machine Service. (2007). The Freedom Car Family: FC20 Shuttle Coal Hauler. Phillips Machine Service. http://www.phillipsmachine.com/pdf/FC20.PDF (accessed December 14, 2009).
Phillips Machine Service 2007d	Phillips Machine Service. (2007). The Freedom Car Family: FC25 Shuttle Coal Hauler. Phillips Machine Service. http://www.phillipsmachine.com/pdf/FC25.PDF (accessed December 14, 2009).



## **NETL Life Cycle Inventory Data – Process Documentation File**

#### **Section III: Document Control Information**

**Date Created:** September 3, 2015

Point of Contact: Timothy Skone (NETL), Timothy.Skone@NETL.DOE.GOV

**Revision History:** 

Original/no revisions

**How to Cite This Document:** This document should be cited as:

NETL (2015). NETL Life Cycle Inventory Data – Unit Process: Shuttle Car

Construction. U.S. Department of Energy, National Energy Technology Laboratory.

Last Updated: September 2015 (version 01). www.netl.doe.gov/LCA

(http://www.netl.doe.gov/LCA)

## **Section IV: Disclaimer**

Neither the U.S. Department of Energy (DOE) National Energy Technology Laboratory (NETL) nor any person acting on behalf of these organizations:

- A. Makes any warranty or representation, express or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this document, or that the use of any information, apparatus, method, or process disclosed in this document may not infringe on privately owned rights; or
- B. Assumes any liability with this report as to its use, or damages resulting from the use of any information, apparatus, method, or process disclosed in this document.

Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by NETL. The views and opinions of the authors expressed herein do not necessarily state or reflect those of NETL.